



# 90 Watt Series

Small Size Desktop Type

STD - X X X ◊ ◊

O / P Voltage ← → O / P Current



### Green Mode

CEC , DoE Level VI , Energy Star , ErP Stage 2 , NRCan  
No Load Power Consumption Less Than 0.21W

### Features :

- IEC/EN/UL 62368-1 & 60950-1
- Smaller size of 129 x 54 x 32mm
- 100-240VAC Universal Input
- Single Output to 90W
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Private Label Marking Available
- Modified and Custom Design Available
- 1 Year Warranty

Model	O/P Voltage	O/P Current	Watt
STD-15060	15.0V	6.00A	90W
STD-16056	16.0V	5.60A	90W
STD-18050	18.0V	5.00A	90W
STD-19047	19.0V	4.74A	90W
STD-20045	20.0V	4.50A	90W
STD-24037	24.0V	3.75A	90W

### Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	1.2A Max.
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C6

### Output

Load Regulation	±5% ( Typical )
Ripple & Noise	1% Vp-p Max. for Output Voltage @ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection
DC Cord	18AWG / 16AWG
Ferrite Core	Yes

### Safety Approvals

CB / UL / cUL / FCC / GS / CE / PSE / BSMI / LPS

### Electrical

Topology	Switching Flyback
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	3.5mA @ 3Pin
Efficiency	DoE Level VI , Energy Star , ErP Stage 2 & NRCan Certified
	EN55032
EMC Standards	EN61000-3-2,3
	EN55024
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

### Environmental

Operating Temperature	0 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

### Mechanical

Case Dimension	L 129 × W 54 × H 32 (mm)
Weight	340g (Ref.)