

**NEW**

**Medical**



# 300 Watt Series

Desktop Type

ATM300A4 -  X X X

P : C14 ←  → O / P Voltage  
A : C18




- Features :**
- IEC/EN/ANSI/AAMI ES60601-1 (Edition 3.2)
  - EMC : IEC60601-1-2 (Edition 4.1)
  - Means of Protection: 2 X MOPP
  - 100-240VAC Universal Input
  - Regulated Output With Low Ripple Noise
  - Safety Agency Requirements and EMI/EMS Certified
  - Modified and Custom Design Available
  - 2 Years Warranty

Output	
Load Regulation	±5% ( Typical )
Ripple & Noise	≤ 1% Vp-p @ Full Load
Transient(Dynamic) Response	0.5mS with 50% Load Change
Start-up Time	< 3,000mS
Hold-up Time	≥ 10mS @ Full Load
Rise Time	< 50mS
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection

Model	O/P Voltage	O/P Current	Watt
ATM300A4- <input type="checkbox"/> 120	12.0V	24.0A	288W
ATM300A4- <input type="checkbox"/> 150	15.0V	20.0A	300W
ATM300A4- <input type="checkbox"/> 240	24.0V	12.5A	300W

Input	
Voltage	100-240VAC
Line Frequency	50-60Hz
Current	3.5A-1.5A
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C14,C18



Electrical	
Topology	LLC
Dielectric Withstand	4,000VAC Primary - Secondary
Touch Current (Patient) Leakage Current	< 100µA
Earth Leakage Current	< 5mA
Efficiency	Meet DoE Level VI
EMC Standards	EN55011
	EN61000-3-2,3
	EN61000-4-2,3,4,5,6,8,11
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental	
Operating Temperature	-20 to + 40°C
Storage Temperature	-20 to + 80°C
Operating Altitude	5,000M
Relative Humidity	Operating : 20 to 80% RH
	Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical	
Case Dimension	L 204 × W 94 × H 43.5 (mm)
Weight	1,110g (Ref.)